

WIZARD GOLD MIG 630I



MIG (HEAVY INDUSTRY)

- MIG/MMA
- CAPABLE OF LOADING UP TO 15 kg Separated Spool
- Closed type 4 rolls wire feeder is available
- Heavy industrial
- Water Cooler, trolley optional

MIG (Built IN)

- MIG/MAG
- Lift-arc TIG
- Gas/Gasless FCAW
- Built-in hot start
- Inching
- Slow-feeding
- Current and voltage meters
- Burn-back function
- Capable of loading up 15 kg spool built in
- IGBT inverter technology
- Strict three-proff design: PCB glue filling
airway isolation and airway sealing



Three-Phase Frequency

DC

CCC

CE

Technical Parameters	MIG630I
Rated Input Voltage	3P415V ±15%
Frequency (KHz)	50/60
Input Current (A)	60.5
Rated Input Capacity (KVA)	40
No-Load Voltage	77
Duty Cycle (%)	60
Adjustment Current Range (A)	40-630
Adjustment Current Range (V)	14-50
Wire Feeder	Separated Type
Wire Diameter (MM)	0.8/1.2/1.6
Spool Size (Kg)	15
Real Current (A)	630
Protection Classification	IP21S
Net Weight (KG)	45
Machine Dimensions (MM)	620*310*600

FEATURES

New Design, Smart Appearance
Compact Size, Lightweight and Power Saving

Strong Current Output, Superior Arc Performance
Quality Weld with Precise Control